

INTOP[®]

— JAPAN TECHNOLOGY —



0909254154
0908706679



.....



21/20/77 Le Cong Phep,
An Lac Ward,
Binh Tan Dist , Hochiminh City

THUAN HIEP THANH CO., LTD

PWZ

Automatic Self-priming Peripheral Pump



APPLICATIONS FIELDS

Suitable for transferring water without abrasive particles or other whose properties are similar to water. Widely used in living water supply, water tower supply, well water lifting, automatic irrigation system, various corollary equipment, etc.

APPLICATIONS LIMITS

Suction head: 9m
pH: 6.5~8.5
Liquid temperature: 0°C ~ +90°C
Max. working pressure: 6bar
Ambient temperature: 0°C ~ +40°C
Voltage fluctuation: ±10%

PUMP

Pump body: Cast Iron
Coupling: Cast Iron
Impeller: Brass
Mechanical seal: EPDM/Ceramic
Electrophoretic pump body and coupling

MOTOR

Protection: IP44
Insulation: Class B
Continuous service S1
Motor Case: Aluminum
Built-in thermal protector
Copper winding
C&U bearing
SS304 welding shaft

PERFORMANCE DATA

(50Hz n=2900rpm)

Model	Power W	Power HP	Max Flow L/min	Max Head m	Inlet/Outlet mm	Suction Max m
PWZ200	200	0.27	33	24	34/34	8
PWZ400	400	0.54	37	30	34/34	8