

SHAKTI

FIRE FIGHTING PUMPS





With gauge

Detail

Replaceable membrane pressure tanks

Carbon steel flange

Working temperature

Butyl: -20°C/99°C

Epdm: -20°C/99°C

Natural rubber: 0°C/77°C

Model	MAX. Pressure (bar)	Diameter (mm)	Height (mm)	Connector	Precharge Pressure	Packing CBM
SV4L	4	220	200	3/4"	1.5	0.01088
SV8L	4	220	295	3/4"	1.5	0.01569
SV12L	4	290	280	3/4"	1.5	0.02567
SV19L	4	290	400	3/4"	1.5	0.03499
SV24L	6, 8, 10	460	290	1"	1.5	0.03993
SV36L	6, 8, 10	350	550	1"	1.5	0.06738
SV50L	6, 8, 10	350	660	1"	1.5	0.08330
SV60L	6, 8, 10	380	795	1"	1.5	0.13163
SV80L	6, 8, 10	450	740	1"	1.5	0.15390
SV100L	6, 8, 10	450	825	1"	1.5	0.17010
SV200L	10, 16	628	1080	1 1/2"	2	0.46898
SV300L	10, 16	628	1400	1 1/2"	2	0.58305
SV500L	10, 16	790	1455	1 1/2"	2	0.93440